Katalog neu-2007.qxd:Katalog neu-2007.qxd 26.06.2007 13:48 Uhr Seite 28

DEUTSCH

Allzweck-Klebeband Sorte 400 „Steinband“

Beschreibung

Allzweck-Klebeband Sorte 400 besteht aus einem strapazierfähigen, wasserdichten und kunststoffbeschichteten Gewebe, einseitig klebend. Beständig gegen Wasser, Öl, mechanische Beschädigungen und viele chemische Einflüsse.

Anwendung

Dieses Band kann für alle denkbaren Zwecke eingesetzt werden, Außen und Innen. Durch große Dehnfähigkeit, hohe Klebkraft und äußerste Schmiegsamkeit ist dieses Band für Maler , Gipser und Stukkateure der Problemlöser für alle Abdeckarbeiten. Ihr zuverlässiger Helfer für Abdeckarbeiten auf Putz und Stein, Sandstrahlarbeiten, Reparaturarbeiten an Schläuchen und Rohren etc. Reparieren von Löchern und Rissen in Planen, Markisen, Segeln etc. wasserdichtes Versiegeln von Behältern, bombenfestes Verpacken von Transportgütern.

Vorsicht: Nicht auf Aluminium, Kunststoff usw. verkleben!

Technische Daten

Träger	PE-beschichtetes Gewebe
Gesamtdicke	170 µ
Dehnung bis Bruch	30 %
Klebkraft auf Stahl	10 N/25 mm
Zugfestigkeit	88 N/25 mm
Klebstoff	Naturkautschuk
Temperaturbeständigkeit	bis 60° C
Kerndurchmesser	76 mm
Farbe	silber
Länge	50 m

Verpackungseinheiten

Bandbreite mm	**Rollen pro Karton**
38	32
50	24
75	16

ENGLISH

All-Purpose Tape Type 400 „stone tape“

Product Description

All-Purpose Tape Type 400 consists of a heavy duty, waterproof and plastics coated fabric, which is adhesive on one side.
Resistant against water, oil, mechanical damage and many chemical influences.

Application

This tape can be used for any kind of application feasible in- and outdoors.
On account of its high tensibility , adhesive strength and best flexibility, this tape is the problem solver for painters and plasterers regarding covering work on stone and plaster.
Your solid assistant for covering work on stone and plaster , sandblasting, repairing of tubes and pipes etc., repairing of cracks and wholes in tarpaulin, awnings, sails, etc., sealing of containers to make them waterproof, to secure packaging of goods in transport.

Attention: Do not apply to aluminium, plastics, etc.!

Technical Data

Carrier	PE-coated cotton
Total thickness	170 µ
Elongation at break	30 %
Adhesion on steel	10 N/25 mm
Tensile strength	88 N/25 mm
Glue	natural rubber
Temperature resistance	up to 60° C
Core diameter	76 mm
Colour	silver
Length 50	m

Packaging

Roll Width mm	**Rolls per carton**
38	32
50	24
75	16

MUSTER SAMPLE