DEUTSCH

Gewebeband „blau“ Sorte 410 UV-beständig

Beschreibung

Das UV-Gewebeklebeband Sorte 410 besteht aus einem strapazierfähigen, reißfesten, wasserdichten, PE-beschichteten Gewebe und ist einseitig klebend. Die Sorte 410 ist mit einem speziellen Kautschukkleber mit hoher UV -Stabilität beschichtet. Die Sorte 410 hat eine hohe Anfangsklebekraft, auch bei niedrigen Temperaturen.

Anwendung

Die Sorte 410 dient als Langzeit-Gewebeklebeband für empfindliche Oberflächen innen und außen. Es besitzt sehr gute V erklebungseigenschaften auf Putz, Holz, Kunststoff und Aluminium und läßt sich rückstandsfrei entfernen. Das Steinband für sicheres Abkleben für den Maler , Stukkateur und Verputzer.

Technische Daten

Träger	PE-beschichtetes Gewebe
Gesamtdicke	300 µ
Dehnung bis Bruch	12 %
Klebkraft auf Stahl	11 N/25 mm
Zugfestigkeit	147 N/25 mm
Klebstoff	Naturkautschuk
Temperaturbeständigkeit	bis 90° C
Kerndurchmesser	76 mm
Farbe	blau
Länge	25 m

Verpackungseinheiten

Bandbreite mm	**Rollen pro Karton**
19	64
25	48
30	40
38	32
50	24

Andere Bandbreiten auf Anfrage

ENGLISH

Cloth Tape „blue“ Type 410 UV Resistant

Product Description

The UV resistant cloth tape T ype 410 consists of a heavy duty , tear- and waterproof, PE-coated cloth and is adhesive on one side. T ype 410 is coated with a special natural rubber glue of high UV stability and tackiness, even at low temperatures.

Application

Type 410 serves as cloth tape for long-term application on sensitive surfaces in- and outdoors. It offers very good adhesive features on plaster, wood, plastics and aluminium, and can be removed without leaving any residues. The stone tape of painters and plasterers choice for secure masking.

Technical Data

Carrier	PE-coated cloth
Total thickness	300 µ
Elongation at break	12 %
Adhesion on steel	11 N/25 mm
Tensile strength	147 N/25 mm
Glue	natural rubber
Temperature resistance	up to 90° C
Core diameter	76 mm
Colour	blue
Length 25	m

Packaging

Roll Width mm	**Rolls per carton**
19	64
25	48
30	40
38	32
50	24

Other roll widths available on request

MUSTER SAMPLE