Katalog neu-2007.qxd:Katalog neu-2007.qxd 26.06.2007 13:48 Uhr Seite 32

DEUTSCH

Gitterband selbstklebend Sorte 450

Beschreibung

Die Sorte 450 besteht aus einem reißfesten Glasfasergewebe, das mit einem aggressiven Kleber mit hoher Anfangshaftung ausgerüstet ist.

Anwendung

Das Gitterband dient vorwiegend zur Stoßkantenüberbrückung beim Zusammenfügen von Gipskartonplatten. Es dient aber auch bei der Reparatur von Rissen und Löchern. Die Anwendung ist schnell, einfach und rationell.

Technische Daten

Träger	Glasfasergewebe
Flächengewicht	Rohware 43 g/m^2 Fertigware 65 g/m^2
Zugfestigkeit	Kette 325 N/25 mm Schuß 100 N/25 mm
Klebstoff	Hotmelt
Kerndurchmesser	50 mm
Farbe	weiß

Verpackungseinheiten

Bandbreite mm	**Länge**	**Rollen pro Karton**
50	20 m	60
50	45 m	54
50	90 m	24

ENGLISH

Grid-Tape self-adhesive Type 450

Product Description

Type 450 is made of a tear proof fibreglass reinforcement, equipped with an aggressive glue of high tackiness.

Application

The Grid-Tape mainly serves to bridge joints of gypsum plaster boards. But it is also useful for repairing of cracks and wholes. Application is rapid, easy and efficient.

Technical Data

Carrier	fiberglass mesh
Area weight	raw material 43 g/m^2 finished material 65 g/m^2
Tensile strength	warp 325 N/25 mm weft 160 N/25 mm
Glue	hotmelt
Core diameter	50 mm
Colour	white

Packaging

Roll Width mm	**Length**	**Rolls per carton**
50	20 m	60
50	45 m	54
50	90 m	24

MUSTER SAMPLE