

**Technische Produktinformation:
Artikel-Nr. 911-20AX Polyimide Film Silicone Tape**

Technical Data:	Normal	Minimum	Test method
Adhesive	Silicone		
Carrier	Polyimide Film		
Carrier Thickness (mil/mm)	1,00 / 0,025		ASTM D 1000
Total Thickness (mil/mm)	2,56 / 0,064	2,48 / 0,062	ASTM D 1000
Color	Amber		
Adhesion to Steel (N/25mm)/(g/25mm)/(oz/in)	7,0 / 710 / 25	5,6 / 570 / 19,9	ASTM D 1000
Tensile Strength (N/25mm)/(g/25mm)/(oz/in)	118 / 12 / 26	98 / 10 / 22	ASTM D 1000
Elongation (%)	80	60	ASTM D 1000
Dielectric Strength (kV)	6,5	6,0	ASTM D 149
Class of Insulation (°C)	UL H / 200		UL 510
Range of Temperature (°C/°F)	-73 ~ 260 / -100 ~ 500		
Size:			
Tape Length (m)	33		
Tape Width (mm)	1000 available		

Features: #911-20AX is manufactured from high performance polyimide film with special silicone adhesive. Meet UL 510. With temperature rating for flame retarding to 200 °C / 392 °F. It is also designed for insulating coil at high temperature as well as for the application of generator, capacitor, transformer, etc.

- Excellent mechanical and electric properties
- High conformability
- Good adhesive property, excellent holding and wrapping request

Note: The above data should be considered representative only and should not be used for specification purposes.